

- Provides reliable power distribution to multiple devices
- 1U form factor for horizontal or vertical rack installation
- Individual real-time current measurements (Amp)
- Total active power measurements
- Scheduled On/Off control capability for all outlets
- Sequential turn-on outlets delay setting to prevent high peak current
- RS-232/USB and SNMP multiple communications



PDU PRODUCT SPECIFICATION

MODEL	FSP372PDU-230
Nominal Voltage	220/230/240 Vac
Form Factor	1U
Input Plug Type	1 x IEC C20 (16 A) connector and 1x plug cable
Cord Length	1.8m
Output Receptacle	8 x IEC C13, 10A sockets
ELECTRICAL	
Rated I/P current	16A
Rated I/P voltage range	184 - 300Vac
Power Capacity	3.68kVA @ 230Vac
Output Current Accuracy	± 0.1A
Overload protection	16A Breaker
INDICATORS	
LED Indicators	PDU power LED and fault LED
LCD Display	Indicates outlet On/Off status, input voltage & current, outlet current and fault/alarm code
PHYSICAL	
Dimension, D x W x H (mm)	250 x 430 x 44
Net Weight (kgs)	3.5
Color	Black
ENVIRONMENT	
Operating Temperature	20-90 % RH @ 0- 50°C (non-condensing)
Altitude	< 1000m
Conformance	
EMC	EN 55022 Class B EN 61000-3-2 EN 61000-3-3 EN 55024
Safety	EN 60950-1

* Product specifications are subject to change without further notice